



More information on the website  
[mirror.radwag.com/en/info,w1,080](http://mirror.radwag.com/en/info,w1,080)

# AK-5/100.STENT Automatic Balance for Stents

WL-506-0001



The drawings, photos and graphics used are for illustrative purposes only.

## Datasheet

Metrological parameters	
Maximum capacity [Max]	5.1 g
Readability [d]	0.1 µg
Tare range	-5.1 g
Minimum weight (USP)	0.8 mg
Minimum weight (U=1%, k=2)	0.08 mg
Standard repeatability [Max]	1 µg
Standard repeatability [5% Max]	0.8 µg
Permissible repeatability [Max]	2 µg
Permissible repeatability [5% Max]	1.5 µg
Linearity	±5 µg
Adjustment	external
Physical parameters	
Display	10" graphic colour touchscreen
Device dimensions W x D x H	395×195×420 mm

### Physical parameters

Packaging dimensions W x D x H	860×800×550 mm
Net weight	20 kg
Gross weight	30 kg

### Communication interface

Communication interface	2×USB-A, USB-C, RS 232 (COM3), HDMI, Ethernet, Wi-Fi, Hotspot
-------------------------	---

### Electrical parameters

Power supply	100 – 240 V AC 50/60 Hz
--------------	-------------------------

\* Wi-Fi® is a registered trademark of Wi-Fi® Alliance.



## Accessories (Additional Fee)

Receipt Printer  
Fingerprint Reader

Additional modules