



More information on the website  
[mirror.radwag.com/us/info,w1,080](http://mirror.radwag.com/us/info,w1,080)

# AK-5/100.STENT Automatic Balance for Stents



The drawings, photos and graphics used are for illustrative purposes only.

## Datasheet

Maximum capacity [Max]	5,1 g
Readability [d]	0,1 µg
Tare range	-5,1 g
Standard repeatability [5% Max]	0,8 µg
Standard repeatability [Max]	1 µg
Standard minimum weight (USP)	0,8 mg
Standard minimum weight (U=1%, k=2)	0,08 mg
Permissible repeatability [5% Max]	1,5 µg
Permissible repeatability [Max]	2 µg
Linearity	±5 µg
Adjustment	external
<b>Physical parameters</b>	
Display	10" graphic colour touchscreen
Device dimensions	395×195×420 mm
Packaging dimensions	860×800×550 mm

Physical parameters	
Net weight	20 kg
Gross weight	30 kg
Communication interface	
2×USB-A, USB-C, HDMI, Ethernet, Wi-Fi, Hotspot	
Power supply	
100 – 240 V AC 50/60 Hz	

\* Wi-Fi® is a registered trademark of Wi-Fi® Alliance.



## Accessories

Receipt Printer  
Fingerprint Reader

Additional modules