



# MYA 5.5Y.F.A Microbalance

WL-109-0024

More information on the website  
[mirror.radwag.com/en/info,w1,0FJ](http://mirror.radwag.com/en/info,w1,0FJ)



The drawings, photos and graphics used are for illustrative purposes only.

## Functions

 Autotest	 Percent Weighing	 Peak hold	 Statistics
 IR sensors	 GLP Procedures	 Air density correction	 Moveable range
 Differential weighing	 Ambient conditions monitoring	 Replaceable unit	 Statistical Quality Control
 ALIBI Memory	 Wi-Fi		

## Datasheet

Metrological parameters	
Maximum capacity [Max]	5.1 g
Minimum load	0.1 mg
Readability [d]	1 µg
Verification unit [e]	1 mg
Tare range	-5.1 g
Standard repeatability [5% Max]	0.6 µg

<b>Metrological parameters</b>	
Standard repeatability [Max]	1.6 $\mu$ g
Standard minimum weight (USP)	1.2 mg
Standard minimum weight (U=1%, k=2)	0.12 mg
Permissible repeatability [5% Max]	1.2 $\mu$ g
Permissible repeatability [Max]	2.4 $\mu$ g
Linearity	$\pm 5$ $\mu$ g
Eccentric load deviation	5 $\mu$ g
Sensitivity time drift	$1 \times 10^{-6}$ /Year $\times$ Rt
Stabilization time	max 8 s
Adjustment	internal (automatic)
OIML Class	I
<b>Physical parameters</b>	
Leveling system	automatic – Reflex Level System
Display	10" graphic colour touchscreen
Weighing chamber doors	automatic
Delivery components	Microbalance, terminal, weighing pan, weighing pan for filters, centring ring, glass lid, power supply, pincette, brush, fabric dust cover.
Weighing chamber dimensions	$\varnothing 93.8 \times 35$ mm
Weighing pan dimensions	$\varnothing 70 + \varnothing 16$ mm
Packaging dimensions W x D x H	750 $\times$ 492 $\times$ 595 mm
Net weight	10.6 kg
Gross weight	16.5 kg
<b>Construction</b>	
Protection class	IP 43
<b>Communication interface</b>	
Communication interface	2 $\times$ USB-A, USB-C, RS 232 (COM3), HDMI, Ethernet, Wi-Fi, Hotspot
<b>Electrical parameters</b>	
Power supply	Adapter: 100 – 240V AC 50/60Hz 1A Max; 15V DC 2.4A Balance: 12 – 15V DC 1.4A max; 9 – 17W*
<b>Environmental conditions</b>	
Operating temperature	+10 – +40 °C
Operating temperature change rate	$\pm 0.3$ °C / 1 h ( $\pm 1$ °C / 8 h)
Relative humidity	40% – 80%
Relative humidity change rate	$\pm 1$ % / h ( $\pm 4$ % / 8 h)

**Repeatability** is expressed as a standard deviation from 10 cycles of mass standard weighing.

**Stabilization time** depends on the ambient conditions and the dynamics of weighing pan loading; specified for FAST profile.

\* Power consumption depends on the terminal configuration as well as the number and type of external devices connected. The power supply can be connected to the socket on the back of the balance housing or to the terminal.

\* Wi-Fi® is a registered trademark of Wi-Fi® Alliance.

## Accessories (Additional Fee)

MediaBox  
RFID Tags  
Antivibration Tables  
Power Adapters  
Additional modules  
Anti-Draft Chamber for Microbalances  
Filter Chamber Tray  
Professional Weighing Tables  
Antistatic ionizer

Protective cover for balances  
Barcode scanners  
RS 232, RS 485 cables  
Label Printers  
THBR 2.0 System - Ambient Conditions Monitoring  
Receipt Printer  
Fingerprint Reader  
RS 232 – USB Converter

## Software (Additional Fee)

- E2R Weighing [WX-010-0099]
- Label Editor R02 [WX-010-0094]
- R-Lab [WX-010-0080]
- RADWAG Development Studio [WX-010-0104]
- RAD Key [WX-010-0005]
- RADWAG Remote Desktop [WX-010-0107]
- Scale Editor 2.1 [WX-010-0173]

## Device dimensions W x D x H

