



More information on the website
mirror.radwag.com/en/info,w1,1P8

C315.4.300.C6 Platform Scale

WP-230-0002



The drawings, photos and graphics used are for illustrative purposes only.

Functions


 Plus/Minus Control

 Percent Weighing

 Totalizing

 Parts counting

 Internal battery

 Peak hold

 Newton unit measurement

 GLP Procedures

 Animal weighing

 ALIBI Memory

Datasheet

| Metrological parameters | |
|--|---------|
| Maximum capacity [Max] | 300 kg |
| Minimum load | 2 kg |
| Readability [d] | 0.1 kg |
| Verification unit [e] | 0.1 kg |
| Tare range | -300 kg |
| Max readability for non-verified scale | 20 g |
| OIML Class | III |

| Physical parameters | |
|--------------------------------|--|
| Display | 4.3" LCD (backlit) |
| Cable length | 3 m |
| Weighing pan dimensions | 800×800 mm |
| Weighing platform height | 116 ± 6 mm |
| Packaging dimensions W x D x H | 900×900×500 mm |
| Scale mass with indicator | 55 kg |
| Construction | |
| Protection class | IP 65 construction, IP 67 cell, IP 43 terminal |
| Communication interface | |
| Communication interface | RS232 |
| Optional interfaces | RS232 |
| Electrical parameters | |
| Power supply | 100 – 240 V AC 50/60 Hz and battery |
| Power consumption max. | 5 W |
| Operation time on batteries | max 8h |
| Environmental conditions | |
| Operating temperature | -10 – +40 °C |
| Relative humidity | 10% – 85% RH no condensation |



Additional fee for verification



Accessories (Additional Fee)

Power Adapters

RS 232 cables (scale - printer)

Stands, wall mounting kits and mounting brackets

Cigarette lighter receptacle power supply cables

Displays

Frame for embedded scales

Ramps

RS 232, RS 485 cables

RS 232 – Ethernet Converter

AP2-1 Current Loop Unit

RS 232 – USB Converter

RS 232 – RS 485 Converter

Receipt Printer

Software (Additional Fee)

• RAD Key [WX-010-0005]

• Scale Editor 2.1 [WX-010-0173]

• R-Lab [WX-010-0080]

Device dimensions W x D x H



| | A | B | H |
|---------|------|------|---------|
| C6 | 800 | 800 | 120 ±10 |
| C7 | 1000 | 1000 | 120 ±10 |
| C8 | 1200 | 1200 | 120 ±10 |
| C8/9 | 1200 | 1500 | 120 ±10 |
| C9 | 1500 | 1500 | 120 ±10 |
| 6000.C9 | 1500 | 1500 | 160 ±10 |