



# High Resolution Platforms PL.32.HRP.EX

WX-009-0272

More information on the website  
[mirror.radwag.com/us/info,w1,7E5](http://mirror.radwag.com/us/info,w1,7E5)



The drawings, photos and graphics used are for illustrative purposes only.

## Datasheet

Maximum capacity [Max]	32 kg
Preload range	4 kg
Readability [d]	0,1 g
Tare range	-32 kg
Repeatability	0,1 g
Linearity	±0,3 g
Adjustment	internal (automatic)
<b>Physical parameters</b>	
Cable length	10 m
Weighing pan dimensions	360×280 mm
Packaging dimensions W x D x H	560×473×370 mm
Net weight	14,6 kg
Gross weight	18,6 kg
<b>Construction</b>	
Protection class	IP 67

Construction	
ATEX Certification	II 3G Ex ic IIB T4 Gc
IECEX Certification	Ex ic IIB T4 Gc
Construction	aluminum
Weighing pan material	Stainless steel AISI304
Communication interface	RS485
Power supply	100 – 240 V AC 50/60 Hz
Operating temperature	+10 – +40 °C
Relative humidity	15% – 80%



## Accessories (Additional Fee)

PUE HX5.EX Weighing Terminal  
Antivibration tables



Ex-Scale-Intended Intrinsically Safe Power Supply for PUE HX5.EX  
Weighing Terminal  
Receipt Printer

## Software (Additional Fee)



- MWMH Manager [WX-010-0103]
- RADWAG Development Studio [WX-010-0104]

- RAD Key [WX-010-0005]

## Device dimensions W x D x H



PL.16 - 32.HRP



PL.62-2000.HRP

Scale type	A1	A2	H
PL.(16-32).HRP	360	280	180±5
PL.(62-150).HRP	500	400	180±5
PL.150.2.HRP	500	500	180±5
PL.(150.1-300).HRP	800	600	180±5
PL.(300.1-1100).HRP	1000	800	180±5
PL.(2000).HRP	1250	1000	180±5

Dimensions in mm