

# XA 21/52.5Y.M.A.P Microbalance

WL-112-1001





The drawings, photos and graphics used are for illustrative purposes only.

### **Functions**

Q	Autotest	%	Percent Weighing	MAX	Peak hold	<u>l</u>	Statistics
4	IR sensors	GLP	GLP Procedures	1	Pipettes Calibration	≋	Air density correction
<b>(</b>	Automatic sliding door	njimiji <del>                                      </del>	Moveable range		Differential weighing		Ambient conditions monitoring
<b>f</b>	Replaceable unit	SQC	Statistical Quality Control		ALIBI Memory		Wi-Fi


# **Datasheet**

Maximum capacity [Max]	21 / 52 g
Minimum load	0,1 mg
Readability [d]	1 / 5 µg
Verification unit [e]	1 mg
Tare range	-52 g
Standard repeatability [5% Max]	1,5 μg

Standard repeatability [Max]	6 µg					
Standard minimum weight (USP)	3 mg					
Standard minimum weight (U=1%, k=2)	0,3 mg					
Permissible repeatability [5% Max]	2,4 μg					
Permissible repeatability [Max]	8 µg					
Linearity	±20 μg					
Eccentric load deviation	20 μg					
Sensitivity time drift	1×10 <sup>-6</sup> /Year×Rt					
Stabilization time	~ 3,5 s					
Adjustment	internal (automatic)					
OIML Class	I					
Physical parameters						
Leveling system	automatic – Reflex Level System					
Display	10" graphic colour touchscreen					
Weighing chamber doors	automatic					
Delivery components	Microbalance, weighing pan, weighing pan shield, power supply, automatic pipette calibration adapter: (base, bottom ring, glass vessel, pipette calibration adapter, evaporation ring, weighing pan, glass lid, mechanical closing cover, protecting screw), brush, fabric dust cover.					
Weighing chamber dimensions	199×170×217 mm					
Capacity	11 ml					
Weighing pan dimensions	ø26 mm					
Packaging dimensions W x D x H	750×492×595 mm					
Net weight	14,5 kg					
Gross weight	18,9 kg					
Construction						
Protection class	IP 43					
Communication interface	2×USB-A, USB-C, RS 232 (COM3), HDMI, Ethernet, Wi-Fi, Hotspot					
Power supply	Adapter: 100 – 240V AC 50/60Hz 1A; 15V DC 2,4A Balance: 12 – 15V DC 1,4A max*					
Operating temperature	+10 - +40 °C					
Operating temperature change rate	±0,3 °C / 1 h (±1 °C / 8 h)					
Relative humidity	40% - 80%					
Relative humidity change rate	±1% / h (±4% / 8 h)					
Repeatability is expressed as a standard deviation from 10 cycles of mass standard weighing.						

Stabilization time depends on the ambient conditions and the dynamics of weighing pan loading; specified for FAST profile.

<sup>\*</sup> Wi-Fi® is a registered trademark of Wi-Fi® Alliance.



<sup>\*</sup> The power supply can be connected to the socket on the back of the balance housing or to the terminal.

### **Accessories (Additional Fee)**

MediaBox RFID Tags Antivibration

Antivibration tables Power Adapters

Protective cover for balances

Additional modules

Anti-Draft Chamber for Microbalances Automatic Variable-Volume Pipettes Professional Weighing Tables

Barcode scanners

Workstation for pipettes calibration RS 232, RS 485 cables Label Printers THBR 2.0 System - Ambient Conditions Monitoring Anti-Draft Chamber for XA 4Y and XA 5Y Balances Antistatic ionizer Receipt Printer Fingerprint Reader RS 232 – USB Converter Under-pan weighing

# **Software (Additional Fee)**

- E2R Weighing [WX-010-0099]
- R-Pipettes [WX-010-0026]
- RADWAG Remote Desktop [WX-010-0107]
- RADWAG Development Studio [WX-010-0104]

- RAD Key [WX-010-0005]
- Label Editor R02 [WX-010-0094]
- Scale Editor EWAG 2.1 [WX-010-0173]