



More information on the website
mirror.radwag.com/us/info,w1,ASO

C32.20.PM Precision Balance

WL-223-0079



The drawings, photos and graphics used are for illustrative purposes only.

Functions



Labelling



Plus/Minus Control



Percent Weighing



Totalizing



Parts counting



Newton unit measurement



Statistics



IR sensors



Under-pan weighing



GLP Procedures



Animal weighing



Density determination



Replaceable unit



ALIBI Memory

Datasheet

Maximum capacity [Max]	20 kg
Minimum load	-
Preload range	2 kg
Readability [d]	0,01 g
Tare range	-20 kg
Minimum weight (USP)	8,2 g

Minimum weight (U=1%, k=2)	0,82 g
Repeatability (Max)	0,02 g
Repeatability (5% Max)	0,0041 g
Linearity	±0,03 g
Stabilization time	1,5 s
Adjustment	internal (automatic)
OIML Class	-
Physical parameters	
Leveling system	manual
Display	5" graphic colour
Weighing pan dimensions	200×185 mm
Packaging dimensions W x D x H	520×520×280 mm
Net weight	11,3 kg
Gross weight	13 kg
Construction	
Protection class	IP 43
Communication interface	2×RS232, USB-A, USB-B, Ethernet, 4 IN / 4 OUT (digital), Wi-Fi
Power supply	100 - 240 V AC 50 / 60 Hz
Power consumption max.	0,5 A
Operating temperature	+10 – +40 °C

* Wi-Fi® is a registered trademark of Wi-Fi® Alliance.



Accessories (Additional Fee)

Displays
 Antivibration tables
 Power Adapters
 RS 232 cables (scale - printer)
 Cigarette lighter receptacle power supply cables
 Professional Weighing Tables

Barcode scanners
 Under-pan weighing
 RS 232, RS 485 cables
 Stands, wall mounting kits and mounting brackets
 Receipt Printer
 AP2-1 Current Loop Unit

Software (Additional Fee)

- E2R Weighing [WX-010-0099]
- Label Editor R02 [WX-010-0094]
- Scale Editor - EWAG 2.1 [WX-010-0173]

- RAD Key [WX-010-0005]
- Alibi Reader PC Software [WX-010-0114]
- RADWAG Development Studio [WX-010-0104]

Device dimensions W x D x H

