



More information on the website
mirror.radwag.com/us/info,w1,BRX

AS 3100.X7 Analytical Balance

WL-113-0006



The drawings, photos and graphics used are for illustrative purposes only.

Functions

-  Autotest
-  Dosing
-  Plus/Minus Control
-  Percent Weighing
-  Parts counting
-  Peak hold
-  Formulation
-  Newton unit measurement
-  Statistics
-  Checkweighing
-  IR sensors
-  Under-pan weighing
-  GLP Procedures
-  Animal weighing
-  Density determination
-  Ambient conditions monitoring
-  Replaceable unit
-  Statistical Quality Control
-  ALIBI Memory
-  Drying modes
-  Samples drying
-  Moisture content analysis
-  Dry mass determination
-  Mass for titrator
-  Wi-Fi

Datasheet

Maximum capacity [Max]

3100 g

| | |
|--|--|
| Minimum load | - mg |
| Readability [d] | 1 mg |
| Verification unit [e] | - |
| Tare range | -3,1 kg |
| Standard repeatability [5% Max] | 0,5 mg |
| Standard repeatability [Max] | 0,6 mg |
| Standard minimum weight (USP) | 1 g |
| Standard minimum weight (U=1%, k=2) | 100 mg |
| Permissible repeatability [5% Max] | 0,8 mg |
| Permissible repeatability [Max] | 1 mg |
| Linearity | ±4 mg |
| Stabilization time | 2 s |
| Adjustment | internal (automatic) |
| OIML Class | - |
| Physical parameters | |
| Leveling system | semi-automatic – LevelSENSING |
| Display | 7" graphic colour touchscreen |
| Weighing chamber doors | manual |
| Delivery components | Balance, weighing pan, weighing pan shield, centring ring, bottom cover, power supply. |
| Weighing chamber dimensions | 190×190×222 mm |
| Weighing pan dimensions | ø90 mm (open-work pan) |
| Packaging dimensions W x D x H | 490×400×520 mm |
| Net weight | 9,7 kg |
| Gross weight | 11 kg |
| Construction | |
| Protection class | IP 43 |
| Database capacity | Products, Users, Packaging, Customers, Formulations, Formulations reports, Ambient Conditions, Weighings, Alibi memory |
| Features of use | |
| Touch-free operation | 2 IR Sensors |
| Communication interface | 2×RS232 ¹ , 2×USB-A (interchangeable), USB-B, Wi-Fi, Ethernet |
| Power supply | Adapter: 100 – 240V AC 50/60Hz 0.6A Max; 12V DC 1,2A Balance: 12 – 15V DC 0,9A max; 4 – 8W* |
| Power consumption max. | 4 W |
| Operating temperature | +10 – +40 °C |
| Ambient conditions monitoring (option) | THBR 2.0 System, THBR BOX, THB P, THB W, THB S |
| Relative humidity | 40% – 80% |

Repeatability is expressed as a standard deviation from 10 weighing cycles.

Stabilization time depends on the ambient conditions and the dynamics of weighing pan loading; specified for FAST profile.

¹ Barcode scanners, available as weighing instrument accessory, communicate with the instrument via RS232 interface exclusively.



Accessories (Additional Fee)

Antivibration tables
Holders for laboratory flasks
Power Adapters
Cigarette lighter receptacle power supply cables
Density determination KIT
USB cable (scale - printer)
Professional Weighing Tables
Barcode scanners
Holders for test tubes and filters
Workstation for pipettes calibration
RS 232, RS 485 cables

THBR 2.0 System - Ambient Conditions Monitoring
Displays
Protective cover for balances
Weighing dishes
Antistatic ionizer
Receipt Printer
Additional modules
Under-pan weighing
RS 232 cables (scale - printer)
RS 232 – RS 485 Converter

Software (Additional Fee)

• RAD Key [WX-010-0005]
• Scale Editor - EWAG 2.1 [WX-010-0173]

• Alibi Reader PC Software [WX-010-0114]
• RADWAG Development Studio [WX-010-0104]

Device dimensions W x D x H

