



More information on the website  
[mirror.radwag.com/en/info,w1,CGF](http://mirror.radwag.com/en/info,w1,CGF)

# C315.4.600.C8/9 Platform Scale

WP-230-0013




The drawings, photos and graphics used are for illustrative purposes only.

## Functions

 Plus/Minus Control

 Percent Weighing

 Totalizing

 Parts counting

 Internal battery

 Peak hold

 Newton unit measurement

 GLP Procedures

 Animal weighing

 ALIBI Memory

## Datasheet

| Metrological parameters                |         |
|----------------------------------------|---------|
| Maximum capacity [Max]                 | 600 kg  |
| Minimum load                           | 4 kg    |
| Readability [d]                        | 0.2 kg  |
| Verification unit [e]                  | 0.2 kg  |
| Tare range                             | -600 kg |
| Max readability for non-verified scale | 50 g    |
| OIML Class                             | III     |

| Physical parameters            |                                                |
|--------------------------------|------------------------------------------------|
| Display                        | 4.3" LCD (backlit)                             |
| Cable length                   | 3 m                                            |
| Weighing pan dimensions        | 1200×1500 mm                                   |
| Weighing platform height       | 120 ± 10 mm                                    |
| Packaging dimensions W x D x H | 1600×1300×500 mm                               |
| Scale mass with indicator      | 135 kg                                         |
| Construction                   |                                                |
| Protection class               | IP 65 construction, IP 67 cell, IP 43 terminal |
| Communication interface        |                                                |
| Communication interface        | RS232                                          |
| Optional interfaces            | RS232                                          |
| Electrical parameters          |                                                |
| Power supply                   | 100 – 240 V AC 50/60 Hz and battery            |
| Power consumption max.         | 5 W                                            |
| Operation time on batteries    | max 8h                                         |
| Environmental conditions       |                                                |
| Operating temperature          | -10 – +40 °C                                   |
| Relative humidity              | 10% – 85% RH no condensation                   |



Additional fee for verification



## Accessories (Additional Fee)

Power Adapters

RS 232 cables (scale - printer)

Stands, wall mounting kits and mounting brackets

Cigarette lighter receptacle power supply cables

Frame for embedded scales

Displays

Ramps

RS 232, RS 485 cables

RS 232 – Ethernet Converter

AP2-1 Current Loop Unit

RS 232 – USB Converter

RS 232 – RS 485 Converter

Receipt Printer

## Software (Additional Fee)

• RAD Key [WX-010-0005]

• Scale Editor 2.1 [WX-010-0173]

• R-Lab [WX-010-0080]

## Device dimensions W x D x H



|         | A    | B    | H       |
|---------|------|------|---------|
| C6      | 800  | 800  | 120 ±10 |
| C7      | 1000 | 1000 | 120 ±10 |
| C8      | 1200 | 1200 | 120 ±10 |
| C8/9    | 1200 | 1500 | 120 ±10 |
| C9      | 1500 | 1500 | 120 ±10 |
| 6000.C9 | 1500 | 1500 | 160 ±10 |