



More information on the website  
[mirror.radwag.com/en/info,w1,CRQ](https://mirror.radwag.com/en/info,w1,CRQ)

# PS 750.X7.PGC Precision Balance

WK-313-0001



The drawings, photos and graphics used are for illustrative purposes only.

## Functions



Autotest



Dosing



Plus/Minus Control



Percent Weighing



Parts counting



Peak hold



Formulation



Newton unit measurement



Statistics



Checkweighing



IR sensors



Under-pan weighing



GLP Procedures



Animal weighing



Density determination



Ambient conditions monitoring



Replaceable unit



Statistical Quality Control



Packaged Goods Control



ALIBI Memory



Mass for titrator



Wi-Fi

## Datasheet

### Metrological parameters

Maximum capacity [Max]	750 g
Minimum load	0.5 g

<b>Metrological parameters</b>	
Readability [d]	0.01 g
Verification unit [e]	0.01 g
Tare range	-750 g
Minimum weight (USP)	1 g
Minimum weight (U=1%,k=2)	0.1 g
Repeatability (Max)	0.0015 g
Repeatability (5% Max)	0.0005 g
Linearity	±0.003 g
Stabilization time	2 s
Adjustment	internal (automatic)
OIML Class	II
Sensitivity temperature drift	$2 \times 10^{-6} / ^\circ\text{C} \times \text{Rt}$
<b>Physical parameters</b>	
Leveling system	manual
Display	7" graphic colour touchscreen
Delivery components	Balance, weighing pan, weighing pan shield, grounding bumper ×1, bumper ×3, power supply.
Weighing pan dimensions	128×128 mm
Packaging dimensions W x D x H	545×455×575 mm
Net weight	3.9 kg
Gross weight	5 kg
<b>Construction</b>	
Protection class	IP 43
<b>Components and software</b>	
Database capacity	Products, Users, Packaging, Customers, Formulations, Formulations reports, Ambient Conditions, Weighings, Alibi memory, Control reports, Average tares
<b>Features of use</b>	
Touch-free operation	2 IR Sensors
<b>Communication interface</b>	
Communication interface	2×RS232 <sup>1</sup> , USB-A, USB-B, Ethernet, Wi-Fi
<b>Electrical parameters</b>	
Power supply	Adapter: 100 – 240V AC 50/60Hz 0.6A; 12V DC 1.2A Balance: 12 – 15V DC 0.8A max
Power consumption	4 W
<b>Environmental conditions</b>	
Operating temperature	+10 – +40 °C
Relative humidity	40% – 80%

**Repeatability** is expressed as a standard deviation from 10 weighing cycles.

**Stabilization time** depends on the ambient conditions and the dynamics of weighing pan loading; specified for FAST profile.

\* Wi-Fi® is a registered trademark of Wi-Fi® Alliance.



Additional fee for verification



## Accessories (Additional Fee)

Power Adapters

Cigarette lighter receptacle power supply cables

USB cable (scale - printer)

Density determination KIT

Barcode scanners

Anti-Draft Chamber for Balances with a 128×128 mm Weighing Pan

Antivibration Tables

Displays

Draft Shield

Protective cover for balances

Receipt Printer

RS 232, RS 485 cables

Additional modules

Under-pan weighing

RS 232 cables (scale - printer)

RS 232 – RS 485 Converter

## Software (Additional Fee)

- RAD Key [WX-010-0005]
- Alibi Reader [WX-010-0114]
- Scale Editor 2.1 [WX-010-0173]

- E2R PGC [WX-010-0051]
- R-Lab [WX-010-0080]
- RADWAG Development Studio [WX-010-0104]