



More information on the website  
[mirror.radwag.com/ja/info,w1,F5V](http://mirror.radwag.com/ja/info,w1,F5V)

# XA 6.5Y.KO

WL-405-0020



The drawings, photos and graphics used are for illustrative purposes only.



Automatic sliding door



<div style="background-color: #cccccc; height: 15px; width: 100%;"></div>	
E1	100 mg – 5 g
E2	1 mg – 5 g
F1	1 mg – 5 g
F2	1 mg – 5 g
M1	1 mg – 5 g
M2	1 mg – 5 g
[Max]	6 g
[d]	0,001 mg
[5% Max]	1,2 µg
[Max]	2 µg
	3 µg

<b>Dimensions</b>	
Thickness	1d / 1 mm
Weight	0 – 6 g
Response time	5 s
Material	Aluminum (Anodized)
<b>Technical specifications</b>	
Display	10" IPS + 16:9 ratio
Resolution	1600 x 900
Dimensions (mm)	249x170x72
Weight (kg)	15,7
Power consumption (W)	20,1
<b>Connectivity</b>	
Ports	2xUSB-A, USB-C, HDMI, Ethernet, Wi-Fi, Hotspot
<b>Operating conditions</b>	
Operating temperature	+15 – +35 °C
Humidity	±1 °C / 12 h
Storage temperature	40% – 70%
Storage humidity	±5% / 4 h

\* Wi-Fi® is a registered trademark of Wi-Fi® Alliance.



### Optional (Additional Fee)

RFID  
 1D  
 2D  
 3D  
 RS 232/RS 485  
 RS 232/RS 485  
 RS 232/RS 485

THBR 2.0 - 4K - 60Hz  
 XA 4Y/XA 5Y  
 RS 232/RS 485  
 RS 232 (RJ45 - RJ45)

### Optional (Additional Fee)

• [WX-010-0005]  
 • [WX-010-0048]

• [WX-010-0164]