radwag.com

Balkenwaage HX5.EX-1.4P2.600.C

WW-008-0054

More information on the website
mirror.radwag.com/de/info,w1,HR2



The drawings, photos and graphics used are for illustrative purposes only.

Funktionen

- Labelling
- Plus/Minus Control
- Percent Weighing
- Parts counting
- Newton unit measurement
- Statistics
- GLP Procedures
- Replaceable unit
- ALIBI Memory

Technische Daten

Messtechnische Parameter	
Wägebereich [Max]	600 kg
Min. Belastung	4 kg
Ablesbarkeit [d]	200 g
Eichwert [e]	200 g
Tarierbereich	-600 kg
OIML-Klasse	III

Physikalische Parameter	
Display	5” grafisch farbiger
Kabellänge	3 m + 5 m
Waagschale	2 St. 1,2 m
Nettogewicht	43,8 kg
Bruttogewicht	44 kg
Konstruktion	
Schutzart	IP 65 Konstruktion, IP 67 Tensometer, IP 66 / 68 Terminal
Zertifizierung ATEX	II 2G Ex ib IIB T4 Gb
Zertifizierung IECEx	Ex ib IIB T4 Gb
Konstruktion	pulverbeschichteter Stahl St3S
Kommunikationsschnittstellen	
Schnittstellen	2×RS232, RS485
Elektrische Parameter	
Stromversorgung	100 – 240 V AC 50/60 Hz
Maximaler Leistungsaufnahme	15 W
Umgebungsbedingungen	
Umgebungstemperatur	-10 – +40 °C
Relative Luftfeuchtigkeit	10% – 85% RH ohne Kondensation
Messgerät	PUE HX5.EX-1

Additional fee for verification

Zubehör (Additional Fee)

Kommunikationsmodul
Eigensichere Stromversorgung für EX-Waage
Thermische Drucker

Software (Additional Fee)

- E2R Wägung [WX-010-0099]
- Etiketten-Editor R02 [WX-010-0094]
- RLAB [WX-010-0080]
- RADWAG Development Studio [WX-010-0104]
- RAD Key [WX-010-0005]
- Alibi Reader [WX-010-0114]
- Scale Editor 2.1 [WX-010-0173]