



More information on the website  
[mirror.radwag.com/us/info,w1,K8G](http://mirror.radwag.com/us/info,w1,K8G)

# MPS.M.6300.R1 Weighing Module

WX-016-0344



The drawings, photos and graphics used are for illustrative purposes only.

## Datasheet

Metrological parameters	
Maximum capacity [Max]	6300 g
Preload range	630 g
Readability [d]	10 mg
Repeatability	8 mg
Linearity	±20 mg
Warm-up time after connection to power	1 h
Stabilization time	2 s
Adjustment	external
Construction	
Protection class	IP 43
Housing	aluminum
Weighing pan material	aluminum
Communication interface	
Communication interface	RS232

Electrical parameters	
Power supply	Adapter: 100 – 240V AC 50/60Hz 0,6A; 12V DC 1,2A Module: 12V DC
Environmental conditions	
Operating temperature	+10 – +40 °C
Relative humidity	40% – 80%
Physical parameters	
Weighing pan dimensions	ø100 mm
Device dimensions W x D x H	266x70x105 mm
Net weight	1,8 kg



## Accessories (Additional Fee)

RS 232, RS 485 cables  
Antivibration tables

R Terminal (WDM-8)

## Software (Additional Fee)

- R Panel [WX-010-0187]

## Device dimensions W x D x H

