



More information on the website
mirror.radwag.com/it/info,w1,L5U

PM02.EX-1-2 intrinsically safe power supply intended for EX scale

WX-004-0257



The drawings, photos and graphics used are for illustrative purposes only.

Specifiche

Parametri fisici	
Lunghezza del cavo	3 m
Device dimensions L x P x A	216x174x64 mm
Costruzione	
Punteggio IP	IP 66 / 68
Certificazione ATEX	II 2G Ex eb mb [ib] IIC T4 Gb II 2D Ex tb [ib] IIIC T70°C Db
Struttura	Stainless steel
Lavorare in zone	1, 2 (gases); 21, 22 (dusts)
Parametri elettrici	
Alimentatore	100 – 240 V AC 50/60 Hz
Massimo assorbimento elettrico	15 W
Environmental conditions	
Ambiente di lavoro	-20 – +40 °C
Temperatura di stoccaggio	-20 – +60 °C

Environmental conditions

Umidità relativa

10% – 85% RH no condensation






Compatibile con (Additional Fee)

Piattaforme in acciaio inox HRP EX.H
Piattaforme HRP verniciata a polvere

Piattaforme in acciaio inox HRP.H
Piattaforme HRP EX verniciata a polvere

Device dimensions L x P x A



PM01.EX