radwag.com

LDS.1.320.5Y.A Dosing System

WL-601-0009

More information on the website
mirror.radwag.com/en/info,w1,LDS



The drawings, photos and graphics used are for illustrative purposes only.

Functions

- Autotest
- Dosing
- Percent Weighing
- Parts counting
- Peak hold
- Formulation
- Newton unit measurement
- Statistics
- Checkweighing
- IR sensors
- Under-pan weighing
- GLP Procedures
- Animal weighing
- Pipettes Calibration
- Air density correction
- Automatic sliding door
- Density determination
- Differential weighing
- Ambient conditions monitoring
- Statistical Quality Control
- Packaged Goods Control
- ALIBI Memory
- Wi-Fi

Datasheet

Metrological parameters	
Maximum capacity [Max]	320 g
Minimum load	5 mg

Metrological parameters	
Readability [d]	0.05 mg
Tare range	-320 g
Minimum weight (USP)	40 mg
Minimum weight (U=1%, k=2)	4 mg
Standard repeatability [5% Max]	0.02 mg
Permissible repeatability [5% Max]	0.06 mg
Linearity	±0.3 mg
Eccentric load deviation	0.15 mg
Sensitivity time drift	1×10^{-6}/Year×Rt
Stabilization time	1.3 s
Adjustment	internal (automatic)
Physical parameters	
Leveling system	automatic – Reflex Level System
Display	10" graphic colour touchscreen
Weighing chamber	automatic
Weighing chamber doors	automatic
Weighing chamber dimensions	200×170×220 mm
Weighing pan dimensions	ø90 open-work pan + ø85 (option) mm
Construction	
Protection class	IP 43
Communication interface	
Communication interface	2×USB-A, USB-C, RS 232 (COM3), HDMI, Ethernet, Wi-Fi, Hotspot
Electrical parameters	
Power supply	Adapter: 100 – 240V AC 50/60Hz 1A Max; 15V DC 2.4A Balance: 12 – 15V DC 1.6A max; 10 – 19W**
Environmental conditions	
Operating temperature	+10 – +40 °C
Operating temperature change rate	±0.3 °C / 1 h (±1 °C / 8 h)
Relative humidity	20% – 80%
Relative humidity change rate	±1% / h (±4% / 8 h)

*Values for distilled water
Note: Increasing the pressure may adversely affect dosing accuracy.
Standard repeatability [5% Max] and **Standard minimum weight (USP)** are parameters obtained in automatic mode under special laboratory conditions.
Repeatability is expressed as a standard deviation from 10 cycles of mass standard weighing.
Stabilization time dependson the ambient conditions and the dynamics of weighing pan loading; specified for FAST profile.
** Power consumption depends on the terminal configuration as well as the number and type of external devices connected.
The power supply can be connected to the socket on the back of the balance housing or to the terminal.

* Wi-Fi® is a registered trademark of Wi-Fi® Alliance.



Accessories (Additional Fee)

MediaBox
RFID Tags
Antivibration Tables
Power Adapters
Protective cover for balances
RS 232, RS 485 cables
Density determination KIT
Additional modules
Professional Weighing Tables
Barcode scanners
Automatic feeders
Label Printers
THBR 2.0 System - Ambient Conditions Monitoring
Under-pan weighing
Anti-Draft Chamber for XA 4Y and XA 5Y Balances
Weighing dishes
Antistatic ionizer
Receipt Printer
Fingerprint Reader
Suction pumps for liquids
RS 232 – USB Converter
Balance Storage Case

Software (Additional Fee)

• E2R Weighing [WX-010-0099]
• Label Editor R02 [WX-010-0094]
• R-Lab [WX-010-0080]
• RADWAG Development Studio [WX-010-0104]
• RAD Key [WX-010-0005]
• RADWAG Remote Desktop [WX-010-0107]
• Scale Editor 2.1 [WX-010-0173]