



More information on the website  
[mirror.radwag.com/us/info,w1,M65](http://mirror.radwag.com/us/info,w1,M65)

# MAS.440.R1 Weighing Module

WX-016-0365



The drawings, photos and graphics used are for illustrative purposes only.

## Datasheet

Maximum capacity [Max]	640 g
Preload range	64 g
Readability [d]	1 mg
Repeatability	1,5 mg
Linearity	±3 mg
Warm-up time after connection to power	1 h
Stabilization time	2 s
Adjustment	external
<b>Construction</b>	
Protection class	IP 43
Housing	aluminum
Weighing pan material	Stainless steel
Communication interface	RS232
Power supply	Adapter: 100 – 240V AC 50/60Hz; 12V DC 1,2A Module: 12V DC

Operating temperature	+10 – +40 °C
-----------------------	--------------

Relative humidity	40% – 80%
-------------------	-----------

#### Physical parameters

Weighing pan dimensions	ø56 mm
-------------------------	--------

Device dimensions W x D x H	231x115x120 mm
-----------------------------	----------------

Net weight	1,6 kg
------------	--------



## Accessories (Additional Fee)

Antivibration tables  
R Terminal (WDM-8)

RS 232, RS 485 cables

## Software (Additional Fee)

• R Panel [WX-010-0187]