



PS 360.X7 Precision Balance

WL-226-0014

More information on the website
mirror.radwag.com/en/info,w1,N1D



The drawings, photos and graphics used are for illustrative purposes only.

Functions

 Autotest	 Dosing	 Plus/Minus Control	 Percent Weighing
 Parts counting	 Peak hold	 Formulation	 Newton unit measurement
 Statistics	 Checkweighing	 IR sensors	 Under-pan weighing
 GLP Procedures	 Animal weighing	 Density determination	 Ambient conditions monitoring
 Replaceable unit	 Statistical Quality Control	 ALIBI Memory	 Mass for titrator
 Wi-Fi			

Datasheet

Metrological parameters

Maximum capacity [Max]	360 g
Minimum load	20 mg

Metrological parameters	
Readability [d]	1 mg
Verification unit [e]	10 mg
Tare range	-360 g
Standard repeatability [5% Max]	0.5 mg
Standard repeatability [Max]	1 mg
Standard minimum weight (USP)	1 g
Standard minimum weight (U=1%, k=2)	0.1 g
Linearity	±2 mg
Stabilization time	2 s
Adjustment	internal (automatic)
OIML Class	II
Sensitivity temperature drift	$2 \times 10^{-6} / ^\circ\text{C} \times \text{Rt}$
Physical parameters	
Leveling system	manual
Display	7" graphic colour touchscreen
Delivery components	Balance, weighing pan, weighing pan shield, grounding bumper x1, bumper x3, power supply.
Weighing pan dimensions	128x128 mm
Packaging dimensions W x D x H	545x455x575 mm
Net weight	5.7 kg
Gross weight	7.49 kg
Construction	
Protection class	IP 43
Components and software	
Database capacity	Products, Users, Packaging, Customers, Formulations, Formulations reports, Ambient Conditions, Weighings, Alibi memory
Features of use	
Touch-free operation	2 IR Sensors
Communication interface	
Communication interface	2xRS232 ¹ , USB-A, USB-B, Ethernet, Wi-Fi
Electrical parameters	
Power supply	Adapter: 100 – 240V AC 50/60Hz 0.6A; 12V DC 1.2A Balance: 12 – 15V DC 0.8A max
Power consumption	4 W
Environmental conditions	
Operating temperature	+10 – +40 °C
Ambient conditions monitoring (option)	THBR 2.0 System, THBR BOX, THB P, THB W, THB S
Relative humidity	40% – 80%
Repeatability is expressed as a standard deviation from 10 weighing cycles.	
Stabilization time depends on the ambient conditions and the dynamics of weighing pan loading; specified for FAST profile.	
¹ Barcode scanners, available as weighing instrument accessory, communicate with the instrument via RS232 interface exclusively.	

* Wi-Fi® is a registered trademark of Wi-Fi® Alliance.



Additional fee for verification



Accessories (Additional Fee)

Antivibration Tables

Power Adapters

Cigarette lighter receptacle power supply cables

USB cable (scale - printer)

Density determination KIT

Barcode scanners

Anti-Draft Chamber for Balances with a 128x128 mm Weighing Pan

RS 232, RS 485 cables

THBR 2.0 System - Ambient Conditions Monitoring

Displays

Protective cover for balances

Receipt Printer

Additional modules

Under-pan weighing

RS 232 cables (scale - printer)

RS 232 – RS 485 Converter

Software (Additional Fee)

- RAD Key [WX-010-0005]
- R-Lab [WX-010-0080]
- RADWAG Development Studio [WX-010-0104]

- Alibi Reader [WX-010-0114]
- Scale Editor 2.1 [WX-010-0173]

Device dimensions W x D x H

