radwag.com

DWM HPS Checkweigher

WK-105-00__

More information on the website
mirror.radwag.com/en/info,w1,NII



The drawings, photos and graphics used are for illustrative purposes only.

Datasheet

Metrological parameters	
Maximum capacity [Max]	1500 – 6000 g
Minimum load	20 – 100 g
Readability [d]	0.5 – 2 g
Tare range	-1500 – -6000 g
Physical parameters	
Display	12” graphic colour touchscreen
Construction	
Protection class	IP 65
Construction	Stainless steel AISI304
Max. dimensions of sorted product [lenght×width]	350×180 - 500×280 mm
Weighing module	electromagnetic weighing module
Conveyors	belt
Pneumatic connector	6 bar quick coupling intended for 12 mm cable

Communication interface	
Communication interface	Ethernet, USB, RS232, I / O
Electrical parameters	
Power supply	100 – 240 V AC 50/60 Hz
Components and software	
Operating system	Microsoft Windows 11 IoT
Features of use	
Conveyor velocity	1.6 – 1 m/s
Number of separators	6 or 12



Accessories (Additional Fee)

Receipt Printer

Software (Additional Fee)

- Label Editor R02 [WX-010-0094]
- E2R Checkweigher [WX-010-0055]