radwag.com

# HX5.EX-1.4.600.H7 4 Load Cell Platform Scale

WW-009-0007

More information on the website
mirror.radwag.com/en/info,w1,OUD



The drawings, photos and graphics used are for illustrative purposes only.

## Functions

- Labelling
- Plus/Minus Control
- Percent Weighing
- Parts counting
- Newton unit measurement
- Statistics
- GLP Procedures
- Replaceable unit
- ALIBI Memory

## Datasheet

| Metrological parameters | |
|---|---|
| Maximum capacity [Max] | 600 kg |
| Minimum load | 4 kg |
| Readability [d] | 200 g |
| Verification unit [e] | 200 g |
| Tare range | -600 kg |
| OIML Class | III |

| | |
|---|---|
| **Physical parameters** | |
| Display | 5” graphic colour |
| Cable length | 3 m |
| Weighing pan dimensions | 1000×1000 mm |
| Net weight | 87.8 kg |
| Gross weight | 88 kg |
| **Construction** | |
| Protection class | IP 66 / 69 construction, IP 66 / 68 terminal |
| ATEX Certification | II 2G Ex ib IIC T4 Gb<br>II 2D Ex ib IIIC T135°C Db |
| IECEx Certification | Ex ib IIC T4 Gb<br>Ex ib IIIC T135°C Db |
| Construction | Stainless steel AISI304 |
| **Communication interface** | |
| Communication interface | 2×RS232, RS485 |
| **Electrical parameters** | |
| Power supply | 100 – 240 V AC 50/60 Hz |
| Power consumption max. | 15 W |
| **Environmental conditions** | |
| Operating temperature | -10 – +40 °C |
| Relative humidity | 10% – 85% RH no condensation |
| Indicator | PUE HX5.EX-1 |

Additional fee for verification

## Accessories (Additional Fee)

Communication Modules
Ex-Scale-Intended Intrinsically Safe Power Supply for PUE HX5.EX
Weighing Terminal
Receipt Printer

## Software (Additional Fee)

- E2R Weighing [WX-010-0099]
- Label Editor R02 [WX-010-0094]
- R-Lab [WX-010-0080]
- RADWAG Development Studio [WX-010-0104]
- RAD Key [WX-010-0005]
- Alibi Reader [WX-010-0114]
- Scale Editor 2.1 [WX-010-0173]