



More information on the website
mirror.radwag.com/us/info,w1,PES











PUE H315 Weighing Terminal

WX-008-0191



The drawings, photos and graphics used are for illustrative purposes only.

Functions

-  Plus/Minus Control
-  Percent Weighing
-  Totalizing
-  Parts counting
-  Internal battery
-  Peak hold
-  Newton unit measurement
-  GLP Procedures
-  Animal weighing
-  ALIBI Memory

Datasheet

Metrological parameters	
OIML Class	III
Maximum quantity of divisions from converter	838 860 ×10
Maximum quantity of verification units	6000 e
Minimum volatge per verification unit	0,4 μV
Maximum voltage per verification unit	3,25 μV
Minimum load cell impedance	50 Ω
Maximum load cell impedance	1200 Ω

Metrological parameters	
Load cell excitation voltage	5V DC
Maximum increase of signal	39 mV
Connection of load cells	4 or 6 wires + ekran
Physical parameters	
Display	4,3" LCD (backlit)
Device dimensions W x D x H	208×145×80 mm
Packaging dimensions W x D x H	300×250×130 mm
Net weight	2 kg
Gross weight	2,2 kg
Construction	
Protection class	IP 66 / 67 / 69
Keypad	microswitch
Housing	Stainless steel
Communication interface	
Communication interface	RS232, USB
Optional interfaces	RS232 or RS485 or 4IN/4OUT or Ethernet or analog output 4-20 mA
Electrical parameters	
Power supply	100 – 240 V AC 50/60 Hz
Optional power supply	internal rechargeable battery
Operation time on batteries	max 7h
Environmental conditions	
Operating temperature	-10 – +40 °C
Storage temperature	-10 – +50 °C
Relative humidity	10% – 80% RH no condensation
Number of buttons	5
Multiple range	1 or 2 ranges
Additional LCD display	WD-4/1 (option)



Compatible with (Additional Fee)

Waterproof stainless steel platforms
Mild steel powder coated weighing platforms
AP2-4 Current Loop Unit
RS 232 cables (scale - printer)
RS 232, RS 485 cables
Displays
Ethernet cables (scale - Ethernet)
Power Adapters

USB adapter
Receipt Printer
Additional modules
USB cable (scale - printer)
Stands, wall mounting kits and mounting brackets
RS 232 – USB Converter
RS 232 – RS 485 Converter

Software (Additional Fee)

Device dimensions W x D x H

