



More information on the website
mirror.radwag.com/us/info,w1,QOK

IM01.EX-9/3 Communication Module

WX-016-0188



The drawings, photos and graphics used are for illustrative purposes only.

Datasheet

Construction	
Protection class	IP 66 / 68 (1,5m)
ATEX Certification	II (2)G [Ex ib] IIC Gb II (2)D [Ex ib] IIIC Db
Housing	aluminum
Communication interface	
2×RS232, USB, 12IN / 12OUT, Ethernet IP	
Power supply	
100 – 240 V AC 50/60 Hz	
Power consumption max.	
10 W	
Operating temperature	
-10 – +40 °C	
Storage temperature	
-20 – +60 °C	
Relative humidity	
10% – 85% RH no condensation	
Physical parameters	
Device dimensions W x D x H	222×146×81 mm
Net weight	1,9 kg

Physical parameters

Gross weight

2,5 kg





Compatible with (Additional Fee)

HX5.EX-1.4P2 H Stainless steel Beam Scales
HX5.EX-1 HR Stainless Steel 1-Load-Cell Platform Scales
RS 232 cables (scale - printer)
HX5.EX-1.4P2 C Beam Scales
HX5.EX-1.4N Stainless Steel Ramp Scales
HX5.EX-1.4 C 4-Load-Cell Platform Scales
HX5.EX-1.4P H Stainless steel pallet scales
HX5.EX-1.4 H/Z Stainless steel platform scales, pit version
HX5.EX-1 C 1 Load Cell Platform Scales

HX5.EX-1 H Waterproof Platform Scales
PUE HX5.EX Weighing Terminal
HX5.EX-1.4 H Stainless Steel 4-Load-Cell Platform Scales
RS 232, RS 485 cables
IN/OUT Cables
HX5.EX-1.4P C Pallet scales
USB adapter
USB cable (scale - printer)
RS 232 – USB Converter

Device dimensions W x D x H



IM01.EX