



More information on the website
mirror.radwag.com/ja/info,w1,RXN

PL.150.1.HRP.H

WX-009-0157



The drawings, photos and graphics used are for illustrative purposes only.

Table

Name	
Capacity [Max]	150 kg
Capacity	30 kg
Resolution [d]	1 g
Capacity	-150 kg
Capacity	1,5 g
Capacity	±3 g
Capacity	Capacity (Capacity)
Capacity	
Capacity	IP 66 / 67
Capacity	Capacity AISI304
Capacity	Capacity AISI304
Capacity	
Capacity	RS232, RS485, Ethernet

Technische Daten

Spannung 100 – 240 V AC 50/60 Hz

Umwelt

Temperaturbereich +10 – +40 °C

Luftfeuchtigkeit 15% – 80%

Abmessungen

Frontbreite 800×600 mm

Fronttiefe 1000×800×307 mm

Nettogewicht 71,5 kg

Bruttogewicht 119 kg



Optionen (Additional Fee)

RS 232 Schnittstelle (RJ45 - RJ45)

PUE 7.1 Effizienzklasse

RS 232/RS 485 Schnittstelle

IN/OUT Schnittstelle

Optionen

PUE HY10 Effizienzklasse

PUE HX5.EX Effizienzklasse

RS 232 – USB Schnittstelle

Optionen (Additional Fee)

• MWMH Manager [WX-010-0103]

• RADWAG Development Studio [WX-010-0104]

• RAD Key [WX-010-0005]





PL.16 - 32.HRP.H

PL.62-2000.HRP.H

Scale type	A1	A2	H
PL.(16-32).HRP.H	360	280	180±5
PL.(62-150).HRP.H	500	400	180±5
PL.150.2.HRP.H	500	500	180±5
PL.(150.1-300).HRP.H	800	600	180±5
PL.(300.1-1100).HRP.H	1000	800	180±5
PL.(2000).HRP.H	1250	1000	180±5

Dimensions in mm