radwag.com

# High Resolution Platforms PL.62.HRP

WX-009-0146

More information on the website
mirror.radwag.com/en/info,w1,SPY

The drawings, photos and graphics used are for illustrative purposes only.

## Datasheet

| | |
|---|---|
| **Metrological parameters** | |
| Maximum capacity [Max] | 62 kg |
| Preload range | 30 kg |
| Readability [d] | 0.1 g |
| Tare range | -62 kg |
| Repeatability | 0.08 g |
| Linearity | ±0.4 g |
| Adjustment | internal (automatic) |
| **Construction** | |
| Protection class | IP 67 |
| Construction | mild steel St3S |
| Weighing pan material | Stainless steel AISI304 |
| **Communication interface** | |
| Communication interface | RS232, RS485, Ethernet |

| | |
|---|---|
| **Electrical parameters** | |
| Power supply | 100 – 240 V AC 50/60 Hz |
| **Environmental conditions** | |
| Operating temperature | +10 – +40 °C |
| Relative humidity | 15% – 80% |
| **Physical parameters** | |
| Weighing pan dimensions | 500×400 mm |
| Packaging dimensions W x D x H | 610×710×275 mm |
| Net weight | 30 kg |
| Gross weight | 35 kg |

## Accessories (Additional Fee)

CY10 Scales for PGC
Ethernet cables (scale - Ethernet)
PUE 7.1 Weighing Terminal
RS 232, RS 485 cables
IN/OUT Cables
Powerbanks
PUE HY10 Weighing Terminal
Ex-Scale-Intended Intrinsically Safe Power Supply for PUE HX5.EX
Weighing Terminal
CY10 Precision Balance
RS 232 – USB Converter

## Software (Additional Fee)

• MWMH Manager [WX-010-0103]
• RADWAG Development Studio [WX-010-0104]
• RAD Key [WX-010-0005]

# Device dimensions W x D x H




PL.16 - 32.HRP




PL.62-2000.HRP

| Scale type | A1 | A2 | H |
|---|---|---|---|
| PL.(16-32).HRP | 360 | 280 | 180±5 |
| PL.(62-150).HRP | 500 | 400 | 180±5 |
| PL.150.2.HRP | 500 | 500 | 180±5 |
| PL.(150.1-300).HRP | 800 | 600 | 180±5 |
| PL.(300.1-1100).HRP | 1000 | 800 | 180±5 |
| PL.(2000).HRP | 1250 | 1000 | 180±5 |

Dimensions in mm