



More information on the website
mirror.radwag.com/en/info,w1,TPE

MYA 0.8/3.5Y Microbalance

WL-109-1000



The drawings, photos and graphics used are for illustrative purposes only.

Functions

- Autotest
- Dosing
- Percent Weighing
- Parts counting
- Peak hold
- Formulation
- Newton unit measurement
- Statistics
- Checkweighing
- IR sensors
- GLP Procedures
- Animal weighing
- Pipettes Calibration
- Air density correction
- Density determination
- Moveable range
- Differential weighing
- Ambient conditions monitoring
- Statistical Quality Control
- Packaged Goods Control
- ALIBI Memory
- Wi-Fi

Datasheet

Metrological parameters

| | |
|------------------------|-----------|
| Maximum capacity [Max] | 0.8 / 3 g |
| Minimum load | 0.1 mg |

| Metrological parameters | |
|------------------------------------|---|
| Readability [d] | 1 / 10 µg |
| Verification unit [e] | 1 mg |
| Tare range | -3 g |
| Minimum weight (USP) | 0.82 mg |
| Minimum weight (U=1%, k=2) | 0.082 mg |
| Standard repeatability [5% Max] | 0.41 µg |
| Permissible repeatability [5% Max] | 1.2 µg |
| Linearity | ±3 / 10 µg |
| Eccentric load deviation | 3 / 10 µg |
| Sensitivity time drift | 1×10 ⁻⁶ /Year×Rt |
| Stabilization time | 3.5 s |
| Adjustment | internal (automatic) |
| OIML Class | I |
| Physical parameters | |
| Leveling system | automatic – Reflex Level System |
| Display | 10" graphic colour touchscreen |
| Weighing chamber doors | automatic |
| Delivery components | Microbalance, terminal, weighing pan, weighing pan shield, glass lid, power supply, pincette, brush, fabric dust cover. |
| Weighing chamber dimensions | ø 90×90 mm |
| Weighing pan dimensions | ø16 + ø60 mm |
| Packaging dimensions W x D x H | 750×492×595 mm |
| Net weight | 10.6 kg |
| Gross weight | 16.5 kg |
| Construction | |
| Protection class | IP 43 |
| Communication interface | |
| Communication interface | 2×USB-A, USB-C, RS 232 (COM3), HDMI, Ethernet, Wi-Fi, Hotspot |
| Electrical parameters | |
| Power supply | Adapter: 100 – 240V AC 50/60Hz 1A Max; 15V DC 2.4A Balance: 12 – 15V DC 1.4A max; 9 – 17W* |
| Environmental conditions | |
| Operating temperature | +10 – +40 °C |
| Operating temperature change rate | ±0.3 °C / 1 h (±1 °C / 8 h) |
| Relative humidity | 40% – 80% |
| Relative humidity change rate | ±1% / h (±4% / 8 h) |

Standard repeatability [5% Max], Standard repeatability [Max] and Standard minimum weight (USP) are parameters obtained in automatic mode under special laboratory conditions.

Repeatability is expressed as a standard deviation from 10 cycles of mass standard weighing.

Stabilization time depends on the ambient conditions and the dynamics of weighing pan loading; specified for FAST profile.

* Power consumption depends on the terminal configuration as well as the number and type of external devices connected.

The power supply can be connected to the socket on the back of the balance housing or to the terminal.

* Wi-Fi® is a registered trademark of Wi-Fi® Alliance.

Accessories (Additional Fee)

MediaBox
 RFID Tags
 Antivibration Tables
 Power Adapters
 Additional modules
 Anti-Draft Chamber for Microbalances
 Professional Weighing Tables
 Antistatic ionizer
 Protective cover for balances

Barcode scanners
 Balance Storage Case
 RS 232, RS 485 cables
 Chamber for filter weighing
 THBR 2.0 System - Ambient Conditions Monitoring
 Weighing dishes
 Receipt Printer
 Fingerprint Reader
 RS 232 – USB Converter

Software (Additional Fee)

- E2R Weighing [WX-010-0099]
- Label Editor R02 [WX-010-0094]
- R-Lab [WX-010-0080]
- RADWAG Development Studio [WX-010-0104]

- RAD Key [WX-010-0005]
- RADWAG Remote Desktop [WX-010-0107]
- Scale Editor 2.1 [WX-010-0173]

Device dimensions W x D x H

