



More information on the website  
[mirror.radwag.com/us/info,w1,VLC](http://mirror.radwag.com/us/info,w1,VLC)

# HX5.EX-1.60.H6 One Load Cell Platform Scale

WW-006-0042



The drawings, photos and graphics used are for illustrative purposes only.

## Functions



Labelling



Plus/Minus Control



Percent Weighing



Parts counting



Newton unit measurement



Statistics



GLP Procedures



Replaceable unit



ALIBI Memory

## Datasheet

|                            |                   |
|----------------------------|-------------------|
| <b>Physical parameters</b> |                   |
| Maximum capacity [Max]     | 60 kg             |
| Minimum load               | 400 g             |
| Readability [d]            | 20 g              |
| Tare range                 | -60 kg            |
| OIML Class                 | III               |
| Display                    | 5" graphic colour |

| Physical parameters            |  |
|--------------------------------|--|
| Cable length                   | 2,5 m  |
| Weighing pan dimensions        | 800×800 mm                                   |
| Packaging dimensions W x D x H | 820×1250×490 mm                              |
| Net weight                     | 46,8 kg                                      |
| Gross weight                   | 53 kg  |
| Construction                   |  |
| Protection class               | IP 66 / 67 construction, IP 66 / 68 terminal |
| ATEX Certification             | II 2G Ex ib IIB T4 Gb                        |
| IECEX Certification            | Ex ib IIB T4 Gb                              |
| Construction                   | Stainless steel AISI304                      |
| Weighing pan material          | Stainless steel AISI304                      |
|                                |  |
| Communication interface        | 2×RS232, RS485                               |
|                                |  |
| Power supply                   | 100 – 240 V AC 50/60 Hz                      |
| Power consumption max.         | 15 W   |
|                                |  |
| Operating temperature          | -10 – +40 °C                                 |
| Relative humidity              | 10% – 85% RH no condensation                 |
| Indicator                      | PUE HX5.EX-1                                 |



Additional fee for verification



## Accessories (Additional Fee)

Communication modules  
 Ex-Scale-Intended Intrinsically Safe Power Supply for PUE HX5.EX  
 Weighing Terminal

Receipt Printer

## Software (Additional Fee)

- E2R Weighing [WX-010-0099]
- Label Editor R02 [WX-010-0094]
- Scale Editor - EWAG 2.1 [WX-010-0173]

- RAD Key [WX-010-0005]
- Alibi Reader PC Software [WX-010-0114]
- RADWAG Development Studio [WX-010-0104]