



radwag.com



5Y.20.PM Precision Balance

WL-224-0003

More information on the website
mirror.radwag.com/en/info,w1,XJ0



The drawings, photos and graphics used are for illustrative purposes only.

Functions

Autotest	Dosing	% Percent Weighing	Parts counting
Peak hold	Formulation	Newton unit measurement	Statistics
Checkweighing	IR sensors	Under-pan weighing	GLP Procedures
Animal weighing	Pipettes Calibration	Air density correction	Density determination
Differential weighing	Ambient conditions monitoring	SQC Statistical Quality Control	e Packaged Goods Control
ALIBI Memory	Wi-Fi		

Datasheet

Metrological parameters

Maximum capacity [Max] 20 kg

Minimum load -

Metrological parameters	
Readability [d]	0.01 g
Verification unit [e]	-
Tare range	-20 kg
Standard repeatability [5% Max]	0.004 g
Standard repeatability [Max]	0.015 g
Minimum weight (USP)	8.2 g
Minimum weight (U=1%,k=2)	0.82 g
Linearity	±0.03 g
Stabilization time	1 s
Adjustment	internal (automatic)
OIML Class	-
Physical parameters	
Leveling system	semi-automatic – LevelSENSING
Display	10" graphic colour touchscreen
Delivery components	Precision Balance, weighing pan, fabric dust cover, power supply.
Weighing pan dimensions	200×185 mm
Packaging dimensions W x D x H	520×520×280 mm
Net weight	12 kg
Gross weight	14.2 kg
Construction	
Protection class	IP 43
Communication interface	
Communication interface	2×USB-A, USB-C, RS 232 (COM3), HDMI, Ethernet, Wi-Fi, Hotspot
Electrical parameters	
Power supply	Adapter: 100 – 240V AC 50/60Hz 1A; 15V DC 2.4A Balance: 12 – 15V DC 1.6A max; 10–19W*
Environmental conditions	
Operating temperature	+10 – +40 °C

Repeatability is expressed as a standard deviation from 10 cycles of mass standard weighing.

Stabilization time depends on the ambient conditions and the dynamics of weighing pan loading; specified for FAST profile.

*Power consumption depends on the terminal configuration and the number and type of external devices connected.

* Wi-Fi® is a registered trademark of Wi-Fi® Alliance.



Accessories (Additional Fee)

MediaBox
RFID Tags
Antivibration Tables
Power Adapters
Additional modules

Balance Storage Case
Under-pan weighing
RS 232, RS 485 cables
Stands, wall mounting kits and mounting brackets
Receipt Printer

Professional Weighing Tables
Protective cover for balances
Barcode scanners

Fingerprint Reader
RS 232 – USB Converter

Software (Additional Fee)

- E2R Weighing [WX-010-0099]
- RADWAG Remote Desktop [WX-010-0107]

- Label Editor R02 [WX-010-0094]
- Scale Editor 2.1 [WX-010-0173]

Device dimensions W x D x H

