



More information on the website  
[mirror.radwag.com/us/info,w1,XMT](http://mirror.radwag.com/us/info,w1,XMT)

# HX5.EX-1.60.C3 One Load Cell Platform Scale

WW-006-0014



The drawings, photos and graphics used are for illustrative purposes only.

## Functions



Labelling



Plus/Minus Control



Percent Weighing



Parts counting



Newton unit measurement



Statistics



GLP Procedures



Replaceable unit



ALIBI Memory

## Datasheet

| Metrological parameters |        |
|-------------------------|--------|
| Maximum capacity [Max]  | 60 kg  |
| Minimum load            | 400 g  |
| Readability [d]         | 20 g   |
| Verification unit [e]   | 20 g   |
| Tare range              | -60 kg |
| OIML Class              | III    |

| Physical parameters            |   |
|--------------------------------|---|
| Display                        | 5" graphic colour                       |
| Cable length                   | 2,5 m                                   |
| Weighing pan dimensions        | 500×700 mm                              |
| Packaging dimensions W x D x H | 800×950×270 mm                          |
| Net weight                     | 28,7 kg                                 |
| Gross weight                   | 32,7 kg                                 |
| Construction                   |   |
| Protection class               | IP 65 construction, IP 66 / 68 terminal |
| ATEX Certification             | II 2G Ex ib IIB T4 Gb                   |
| IECEx Certification            | Ex ic IIB T4 Gc                         |
| Construction                   | mild steel St3S                         |
| Weighing pan material          | Stainless steel AISI304                 |
| Communication interface        |   |
| Communication interface        | 2×RS232, RS485                          |
| Electrical parameters          |   |
| Power supply                   | 100 – 240 V AC 50/60 Hz                 |
| Power consumption max.         | 15 W                                    |
| Environmental conditions       |   |
| Operating temperature          | -10 – +40 °C                            |
| Relative humidity              | 10% – 85% RH no condensation            |
| Indicator                      | PUE HX5.EX-1                            |



Additional fee for verification



## Accessories (Additional Fee)

Communication modules  
 Ex-Scale-Intended Intrinsically Safe Power Supply for PUE HX5.EX  
 Weighing Terminal

Receipt Printer

## Software (Additional Fee)

- E2R Weighing [WX-010-0099]
- Label Editor R02 [WX-010-0094]
- Scale Editor - EWAG 2.1 [WX-010-0173]

- RAD Key [WX-010-0005]
- Alibi Reader PC Software [WX-010-0114]
- RADWAG Development Studio [WX-010-0104]