



More information on the website
mirror.radwag.com/en/info,w1,YNJ

THB W Liquid Temperature Sensor

WX-016-0162



The drawings, photos and graphics used are for illustrative purposes only.

Datasheet

Metrological parameters	
Temperature readability [d]	0.01 °C
Temperature measurement accuracy	±0.1
Measured temperature range	+5 – +45 °C
Temperature readability	0.01 °C
Communication interface	USB 2.0
Physical parameters	
Sensor unit dimensions	ø 8×156 mm



Compatible with (Additional Fee)

XA 5Y.M.A.P Microbalance for pipettes calibration
 MYA 5Y.P Microbalance for pipettes calibration
 MYA 5Y.F Microbalance for Filters
 AS X7 Analytical Balance

Density Measurement
 MYA 5Y Microbalance
 XA 5Y Analytical Balance
 Manual susceptometers - Magnetization

XA 5Y.M.A Microbalance
XA 5Y.A Analytical Balance
WAY 5Y.KO Manual Mass Comparator
AS 5Y Analytical Balance
AK-4 Automatic Mass Comparator
PS 5Y Precision Balance
PS 5Y Balances for PGC
AKM-2 Automatic Mass Comparator
XA 5Y.F Analytical Balance for Filters
UMA Automatic Mass Comparator
PS X7 Precision Balance
APP 5Y.KO Manual Mass Comparator
Robotic Mass Comparators

5Y.PM.KB Manual Mass Comparator
HRP 5Y.KO Mass Comparator
Workstation for Pipettes Calibration
Automatic Vacuum Mass Comparators
Automatic susceptometers - Magnetization
XA 5Y.KO Manual Mass Comparator
HRP 5Y.KB Mass Comparator
THBR 2.0 System - Ambient Conditions Monitoring
XA 5Y.M Microbalance
UYA 5Y.KO Manual Mass Comparator
Nano-Comparator NANO.AK-4.500.5Y
XA 5Y.M.A.S Microbalance for stents weighing

Software (Additional Fee)

• THB-R [WX-010-0122]