



More information on the website  
[mirror.radwag.com/en/info,w1,9AB](http://mirror.radwag.com/en/info,w1,9AB)

### MYA 11.1.5Y Microbalance



MYA 11.1.5Y Microbalance

The drawings, photos and graphics used are for illustrative purposes only.

## Functions



Autotest



Dosing



Percent Weighing



Parts counting



Peak hold



Formulation



Newton unit measurement



Statistics



Checkweighing



IR sensors



GLP Procedures



Animal weighing



Pipettes Calibration



Air density correction



Density determination



Differential weighing



Ambient conditions monitoring



Statistical Quality Control



Packaged Goods Control



ALIBI Memory



Wi-Fi

# Datasheet

	<b>MYA 11.1.5Y Microbalance</b> WL-109-0051
<b>Metrological parameters</b>	
Maximum capacity [Max]	11 g
Minimum load	0,1 mg
Readability [d]	1 µg
Verification unit [e]	1 mg
Tare range	-11 g
Minimum weight (USP)	0,9 mg
Minimum weight (U=1%, k=2)	0,09 mg
Standard repeatability [5% Max]	0,45 µg
Permissible repeatability [5% Max]	1,2 µg
Linearity	±6 µg
Eccentric load deviation	6 µg
Sensitivity time drift	$1 \times 10^{-6} / \text{Year} \times \text{Rt}$
Stabilization time	3,5 s
Adjustment	internal (automatic)
OIML Class	I
<b>Physical parameters</b>	
Leveling system	automatic – Reflex Level System
Display	10" graphic colour touchscreen
Weighing chamber doors	automatic
Delivery components	Microbalance, terminal, weighing pan, weighing pan shield, glass lid, power supply, pincette, brush, fabric dust cover.
Weighing chamber dimensions	ø 90x90 mm
Weighing pan dimensions	ø16 mm
Packaging dimensions W x D x H	750x492x595 mm
Net weight	10,6 kg
Gross weight	16,5 kg
<b>Construction</b>	
Protection class	IP 43
<b>Communication interface</b>	
Communication interface	2xUSB-A, USB-C, RS 232 (COM3), HDMI, Ethernet, Wi-Fi, Hotspot
<b>Electrical parameters</b>	
Power supply	Adapter: 100 – 240V AC 50/60Hz 1A Max; 15V DC 2,4A Balance: 12 – 15V DC 1,4A max; 9 – 17W*
<b>Environmental conditions</b>	
Operating temperature	+10 – +40 °C
Operating temperature change rate	±0,3 °C / 1 h (±1 °C / 8 h)
Relative humidity	40% – 80%
Relative humidity change rate	±1% / h (±4% / 8 h)

Standard repeatability [5% Max], Standard repeatability [Max] and Standard minimum weight (USP) are parameters obtained in automatic mode under special laboratory conditions. Repeatability is expressed as a standard deviation from 10 cycles of mass standard weighing. Stabilization time dependson the ambient conditions and the dynamics of weighing pan loading; specified for FAST profile. \* Power consumption depends on the terminal configuration as well as the number and type of external devices connected. The power supply can be connected to the socket on the back of the balance housing or to the terminal.

\* Wi-Fi® is a registered trademark of Wi-Fi® Alliance.

## Accessories (Additional Fee)

MediaBox  
 RFID Tags  
 Antivibration Tables  
 Power Adapters  
 Additional modules  
 Anti-Draft Chamber for Microbalances  
 Professional Weighing Tables  
 Antistatic ionizer  
 Protective cover for balances

Barcode scanners  
 Balance Storage Case  
 RS 232, RS 485 cables  
 Chamber for filter weighing  
 THBR 2.0 System - Ambient Conditions Monitoring  
 Weighing dishes  
 Receipt Printer  
 Fingerprint Reader  
 RS 232 – USB Converter

## Software (Additional Fee)

E2R System  
 Label Editor R02  
 R-LAB  
 RADWAG Development Studio

RAD-KEY  
 RADWAG Remote Desktop  
 Scales Editor 2.1

## Device dimensions W x D x H

MYA 11.1.5Y Microbalance

